

Wheel diameter must be as originally fitted unless permitted in (the Spec Sheets).

Tires must be mounted following the manufacturers specification for wheel width.

Bodywork may not be modified beyond period specifications to accommodate approved tires.

SVRA Supplemental Tire Regulations

(Not for Gold Medallion Classes)

Revised 1/2023

Since tires are a consumable item, SVRA requires tires that are currently available and are of a reasonable age. There is no doubt that modern tire compounds and construction are vastly improved from what was available to competitors when our cars were originally raced.

The intent of these rules is to specify tires that are a reasonable compromise between the tires raced with during the period and what is currently available. Availability in sufficient sizes to maintain equitable tire performance within the Group and Class structure is of primary importance. We are looking for an appropriate level of dry grip for all the cars in a group, to avoid overloading suspension components.

Tires are evaluated by looking at their aspect ratio, tread pattern, carcass design and wear rating. Some tire sizes/brands are acceptable based on true tire diameter and cross-section regardless of the listed aspect ratio.

Some tires listed have been discontinued. These "Legacy" tires remain on the list as long as the age of the existing stock /sizes remain safe for racing use.

Group 1 - Molded Treaded Tires

Minimum aspect ratio of 60, except as listed on the right, tread depth—no less than 2/32" remaining, at all times, over 75% of the tire.

Note: Bodywork may **NOT** be modified beyond period specifications to accommodate listed tires.

Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model Regulations.

Approved Tires:

Avon Racing: 5.0/22-13, A29 14297 ACB9 only, A46 17680. (A25 and

A30 FF not permitted)

6.0/22-13, A29 514 14198 ACB9 only, A25 FF not

permitted (ACB10 not permitted), CR6ZZ

Goodyear Eagle: 5.00/15 G12A **American Racing:** 18/6.0-10 GT

Hoosier: 5.0-15

Vintage TD, Speedster

19.0x5.0-10, 20.5x6.0-13, 22.5x6.0-13TDR

Vintage FF tires

Any Treaded, DOT approved Tires with a UTQG of 100 or greater with appropriate Speed Rating and a minimum Aspect Ratio of 60

For Toyo RA1's and Nitto NT01's, please see page 6 of this document

Group 2 - Molded Treaded Tires

As listed on right or in the latest Monoposto Racing Rules and Regulations

http://www.monoposto.com/

Shaving or reducing tread depth of tire by any means other than normal on track driving is prohibited.

Approved Tires:

FB:

All Monoposto approved tires

Hoosier: 21.0x9.0-13 R35B, 23.0x12.0-13 R35B

F1, F2, F3, FSV:

Dunlop: L, M, Post Historic CR65 and CR82

Avon: All-Weather H-003—H009

Grooved slicks that meet the Monoposto Racing and SVRA approved tread standard. A template is available. It is the driver's responsibility to ensure that all grooved slicks meet the approved standard.

Formula Jr: Dunlop L-204 Hard Compound. With other tires will be run as Formula C. **Formula Vee:** Treaded tires per Monoposto Racing Rules.

(FF, CF, PCF)

Tires: for all classes (Wet or Dry)

Toyo Proxes R888, 185/60R/13 Toyo Proxes R888, 205/60R/13

Hoosier 135/545-13VFF Hoosier 165/580-13VFF

Avon 5.0/22.0-13 A49 17680, A29 14297 Avon 6.5/23.0-13 A49 17681, A29 14298 (A29 compounds no longer imported, but still legal.)

Dunlop 165/580-13 9092 Formula Ford

Dunlop 135/545-13 CR82 9092 Formula Ford (No longer available)

Group 3 - Molded Treaded Tires

Minimum aspect ratio of 60, except as listed on the right, tread depth—no less than 2/32" remaining, at all times, over 75% of the tire.

Note: Bodywork may **NOT** be modified beyond period specifications to accommodate listed tires.

Note: Please refer to the "Group 3 Description and Class List" for **Porsche 356** tire limitations and requirements.

For Toyo RA1's and Nitto NT01's, please see page 6 of this document

Approved Tires:

Avon Racing: 5.0/22-13, & 6.0/22-13, 6.5/23-13 ACB9 (ACB10 not permitted)

185/70-14 (CR6), CR6ZZ, (A25 FF not permitted)

Dunlop: All "L-series, up to 5.50M-13, 14, 15; 165/580-13 (9092)" FormulaFord"

135/545-13 (No longer available) Goodyear Eagle: 5.00/15 G12A Hoosier: TD TDR and Speedster

22.0x6.0-13, 23.0x6.5-14TDR, 135/545-13 & 165/580-13VFF

Any Treaded, DOT approved Tires with a UTQG of 100 or greater with appropriate Speed Rating and a minimum Aspect Ratio of 60

Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified within the Make and Model Regulations.

Tires may not extend beyond the fender opening.

| Group 4 - Molded Treaded Tires | Approved Tires: | | | | | | |
|--|--|--|-----------------------------|--------------------|------------------------|--|--|
| | | | | | | | |
| Tires may not extend beyond the | Modified Catego | - | | | | | |
| fender opening at the highest point | Dunlop L-series (204 compound). | | | | | | |
| of the tire. | Blockley | | | | | | |
| | Continental | | | | | | |
| | Production Cate | agory: | | | | | |
| | | | ge TD, TDR. Goodyear | Dlug Stro | ak Sports Car Sposials | | |
| | All listed above | pius. noosiei viiita | ge 10, 10k. Goodyear | blue Stre | ak sports car specials | | |
| | | | | | | | |
| Group 5 - Treaded Tires & Slicks | Treaded racing t | ires or approved sti | reet tires with a suitab | le speed r | ating. | | |
| ordap of recauca rines a oriens | | * * | pproved tread pattern | • | 2.06. | | |
| While exact size and aspect ratio are | | ead patterns are: | pproved tredd pattern | J. | | | |
| While exact size and aspect ratio are | | • | 22 trand nattorns | | | | |
| not specified, the entrant must | • | nlop: CR-65 and CR-8 | • | | | | |
| ensure that tire choice is appropriate | Avon: All-weather "H-Pattern", CR6ZZ radial. | | | | | | |
| for the car during the eligibility | Goodyear: G-12A and G7 | | | | | | |
| period. | | It is the driver's responsibility to ensure any grooved slicks meet the approved standard. | | | | | |
| | Sports 2000 cars | s - see Rules publish | ed by the Vintage S2 N | .A. for Sp | ec Tires. | | |
| Group 6 - Molded Treaded Tires | Approved Tires: | List per Make and | Model is Listed below: | | | | |
| Wheels and Tires: | MAKE | MODEL | PRODUCTION PERIOD | CLASS | TIRE GROUP | | |
| | AC Cobra | 260/289 | | (BP) | a | | |
| Tires may not extend beyond the | AC Cobra | FIA 289 | | (AP) | a, b | | |
| fender opening. | AC Cobra | 427 | | (AP) | a, b, c | | |
| | AMX Sports Coupe | 290, 343, 360 | | (BP) | a, b | | |
| Specifically Prohibited for Group 6: | AMC | Javelin | 1968-69 | (TAS) | a, b | | |
| , | AMC | Javelin | 1970-72 | (TAS) | a, b, c | | |
| Any tire not listed in the Approved | Aston Martin | DB4, DB5 | | (BP) | a. | | |
| • • | Chevrolet | Corvette 396, 427 | 1965-67 | (AP) | a, b, c, d | | |
| Tire list | Chevrolet Chevrolet | Corvette 427, 454 Corvette 327 | 1968-72 1963-67 | (AP) | a, b, c, d | | |
| | Chevrolet | Corvette 350 | 1968-72 | (BP) (AP) | a, b | | |
| Wheels may be of an alternate | Chevrolet | Corvette 350 | 1968-72 | (BP) | a, b, c, d a, b, c | | |
| material but must be of period | Chevrolet | Camaro | 1967-69 | (TAS) | a, b, c | | |
| design. They must be the correct | Chevrolet | Camaro | 1970-72 | (TAS) | a, b, c | | |
| diameter and width as specified | Dodge | Dart | | (TAS) | a, b | | |
| within the Make and Model | Dodge | Challenger | 1968-72 | (TAS) | a, b, c | | |
| | Ferrari | 250/275 GT, GTO | | (BP) | a | | |
| Regulations. | Ferrari | 365 GTB/4, 375 | | (BP) | a, b | | |
| | Ford | Falcon | | (TAS) | a, b | | |
| | Ford | Mustang | 1964-67 | (TAS) | a, b | | |
| | Ford | Mustang | 1968-69 | (TAS) | a, b | | |
| | Ford | Mustang BOSS 302 | 1970-72 | (TAS) | a, b, c | | |
| | Ford | Mustang BOSS 429 | 1970-72 | (AP) | a, b, c | | |
| | Griffith | 200/400 | | (AP) | a, b | | |
| | Jaguar | XKE | 1962 + | (AP) | a, b | | |
| | Jaguar | XKE | 1962 + | (BP) | a | | |
| | Mercury | Cougar | 1966-67 | (TAS) | a, b | | |
| | Mercury | Cougar | 1968-69 | (TAS) | a, b, c | | |
| | Plymouth | Valiant, Barracuda | 1964-67 | (TAS) | a, b | | |
| | Plymouth | Barracuda Firebird | 1968-72 1967-69 | (TAS) (TAS) | a, b, c a, b | | |
| | I Dontice | | T201-02 | (IAS) | a. u | | |
| Approved DOT Tires: | Pontiac | | | | | | |
| Approved DOT Tires: | Pontiac | Firebird | 1970-72 | (TAS) | a, b, c | | |
| Approved DOT Tires: Any Treaded, DOT approved Tires | | | | | | | |

| appropriate Speed Rating and a | | | | |
|--|--|---|--|--|
| minimum Aspect Ratio of 60 | Tire Group (a): | Tire Group (b): | | |
| For Toyo RA1's and Nitto NT01's, please see page 6 of this document | Dunlop M Series Goodyear 7.00-15 Vintage S.C. SpecialGoodyear 5.50 & 6.00-15 Vintage S.C. Special Hoosier 26.5/9.5-15 Street TDR/Hoosier 24.0x7.0-15, 25.5x8.0 and 8.5-15 TDR Hoosier 25.5/8.5-15 Street TDR/S (front on | | | |
| | Tire Group (c) | Tire Group (d) | | |
| | | | | |
| | Goodyear 8.00-15 Vintage Sports Car Speci Goodyear 600W-15 | | | |
| | Hoosier 25.5/10.00-15, 27.5/11.00-15 TDR 26.5/11-15 TDR | Hoosier 24.0x8.5-15 TDR Hoosier 25.5/8.5-15 TDR/ | | |
| Group 7 | Approved Tires: | | | |
| | Racing slicks and treaded racing tires. Avon Goodyear Hoosier While exact size and aspect ratio are not specified, entrants must ensure that tire choice is appropriate for the car during the eligibility period. | | | |
| | | | | |
| | | | | |
| | | | | |
| Group 8 - Molded Treaded Tires | Approved tires: | | | |
| Minimum aspect ratio of 45, except certain car Make and Models, which have specific tire requirements listed in their Supplemental Regulations, tread depth—no less than 2/32" | There are no specific sizes listed because of the large diversity of Group 8 cars. All Group 8 cars must use similar sized tires to what was used in the day, which is pre 1973. Using oversized tires is unacceptable and when in question, SVRA's determination shall be the final word. | | | |
| remaining, at all times, over 75% of the tire. | Avon: ACB9, ACB10, CR6ZZ, Goodyear Eagle: 5.50/15 G12 or G12A Hoosier: TDR, VFF & Speedster | | | |
| Wheels may be of an alternate material but must be of period design. They must be the correct diameter and width as specified | Any Treaded, DOT approved Tires with a UTQG of 100 or greater with appropriate Speed Rating and a minimum Aspect Ratio of 45 | | | |
| within the Supplemental Regulations of the Make and Model. | Note: Group 8 must use approved full molded treaded tires, regardless of what specification tires a car may have competed with in a prior race series. | | | |
| Tires may not extend beyond the fender opening. | For Toyo RA1's and Nitto NT01's, please see page 6 of this document | | | |
| Group 9 | Approved tires: | | | |
| Monoposto Racing Rules and Regulations: monoposto.com | Avon Goodyear Hankook Hoosier Suitable and appropriate slicks. | | | |

| Group 10 | Approved Tires: | | |
|---|---|--|--|
| | Avon | | |
| Group 10 cars are expected to have | Hoosier | | |
| only period-correct equipment and | Michelin | | |
| specifications. | Goodyear | | |
| Specifications: | Pirelli | | |
| | Racing SLICKS. While exact size and aspect ratio are not specified, entrants must ensure | | |
| | that tire choice is appropriate for the car during the eligibility period. | | |
| Group 11 | Approved Tires: | | |
| • | Avon | | |
| Group 11 cars are expected to have | Goodyear | | |
| only period-correct equipment and | Hankook | | |
| specifications. | Hoosier | | |
| | Michelin | | |
| | Pirelli | | |
| | Racing SLICKS. While exact size and aspect ratio are not specified, entrants must ensure | | |
| | that tire choice is appropriate for the car during the eligibility period. | | |
| Group 12 | GTU, MP1-4 Approved Tires: Goodyear: DOT Radial, Hoosier: R7, Pirelli Track day Tires | | |
| Tire sizes must be used as listed in | Current CP, DP, EP, GT3, GT4: May use current slick tires with the appropriate sizes | | |
| your cars specific racing series. | Goodyear | | |
| , , | Hankook "Track Day" | | |
| Wheels may be of an alternate | Hoosier | | |
| material but must be of period | Michelin | | |
| design. They must be the correct | Pirelli | | |
| diameter and width as specified | Any Treaded, DOT approved Tires with appropriate Speed Rating | | |
| within your cars specific racing series | , | | |
| , | Cars that use tires sizes not available in the Hoosier R7 line may use racing slicks, these | | |
| Tires may not extend beyond the | tires must have two full depth, parallel grooves installed 3" apart centered on the tire, | | |
| fender opening at the highest point | these grooves may not be biased to one side or the other. | | |
| of the tire. | | | |
| | | | |
| | Note: Crown 12 must use above listed approved times recordless of what | | |
| | Note: Group 12 must use above listed approved tires, regardless of what specification tires may have used in a prior racing series. | | |
| | Group 12, GT1, GTO and GTU may use appropriately sized slick tires. | | |
| | Group 12, G11, G10 and G10 may use appropriately sized sinck tiles. | | |

Toyo RA-1 Wear Depths

Full Tread Depth



Legal minimum tread



Nitto NT01 Wear Depths

Full tread depth



Legal minimum tread



These tires must maintain a minimum of 2/32 tread depth across the complete racing surface of the tire. If any part of the tread is less than 2/32 exiting the track the tire will be considered illegal, flat spots excluded.